



manual

Explicitly highly precise...

that's how this LAMBRECHT sensor for absolute pressure works. It is applicable worldwide in a large altitude range. The measuring system with its seawater resistant, multi-layer paint coated housing is extremely robust.

■ high reliability

Professional Line

- serial output signal
- with factory test certificate
- microprocessor technology

application in civil and military navigation • aviation • professional meteorology e. g. at airports • scientific laboratory applications

(8126 MIL)





Measuring element:		silicon resonator
Measuring range:		351310 hPa
Accuracy:		\pm 0.01 % of the final value \circ \pm 0.13 hPa within the range of -25+60 °C
Long-term stability:		< 100 ppm/ year
Resolution:		0.01 hPa
Range of application:		Altitude o10.000 m • temperatures -40+70 °C
Interface:		RS 485
Supply voltage:		1128 V _{DC}
Current consumption:		20 mA
Housing:		Aluminium guard · RAL 7001 (grey) · IP 65
Dimensions:		205 X 180 X 81 mm
Weight:		2.0 kg with protection guard \cdot sensor module 0.4 kg
Standards:		EMC: EN 50081-1/ 50082-2 · EN 61010 (IEC 1010)
Version:		
32.95665.020 000	(95665U20)	Precision Air-Pressure Sensor Module (without guard)
		Installation kit for mounting into data acquisition unit SYNMET-IND/-LOG
		See chapter "Data logger and Software"

Precision Air-Pressure Sensor



Tel

E-mail

Id-No. 00.08126.475 002